

Star products

明星产品



轻量化车轮

名称：轻量化车轮
规格：22.5*9.00；22.5*8.25
特点：1.产品重量仅为28kg
2.提升燃油经济性，物料强度提升至1500MPa；
3.通过轻量化设计，降低整车重量。
适用车型：中、重卡车

Name: Lightweight wheels
Specification: 22.5X9.00; 22.5X8.25
Features: 1. The weight of the product is only 28kg;
2. The strength of the material is increased to 1500MPa through hot processing process;
3. Meet the demand of light weight of the whole vehicle.
Applicable models: Medium and heavy trucks



质量保障能力

名称：质量保障能力
规格：22.5*9.00；22.5*8.25
特点：1.产品重量仅为31.5kg；
2.独特轻量化造型设计；
3.采用特殊车轮专用超高强度材料。
适用车型：中、重卡车

Name: lightweight wheel
Specification: 22.5X9.00; 22.5X8.25
Features: 1. The weight of the product is only 31.5kg;
2. Unique lightweight design;
3. Using special ultra-high strength steel material for wheels.
Applicable models: Medium and heavy trucks



造型车轮

名称：造型车轮
规格：6Jx17
特点：1.采用特殊研发高强度材料；
2.造型美观，可与铝车轮媲美；
3.成本约为铝车轮三分之一。
适用车型：乘用车（共享汽车、新能源汽车）

Name: Modeling Wheel
Specification: 6X17
Features: 1. special developed high strength steel material is used;
2. beautiful shape, comparable with aluminum wheels;
3. The cost is about one-third of aluminum wheels.
Applicable models: Passenger cars (shared cars, new energy vehicles)

Passenger car wheels - List

乘用车车轮一览表

序号	规格	总成零件号	中心孔直径	螺栓孔		偏距	配用轮胎型号	气门嘴型号		
				数量	型式				直径	分圆距
1	6JX15H2	3000601027	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	43±1	195/65R15	TR44
2	6JX15H2	110601027Q	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ100	38±1	195/65R15	TR44
3	6JX15H2	2K0601027	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	47±1	195/65R15	TR44
4	6JX14H2	191601025K	ƒ57.09±0.074	4	螺 2/6	ƒ15±0.025	ƒ100	38±1	195/65R15	TR44
5	5JX14H2	6R0601027	ƒ57.09±0.074	5	螺 2/6	ƒ15±0.25	ƒ112	28±1	175/70R14	TR44
6	4JX18H2	3000601027A	ƒ57.09±0.074	5	螺 2/6	ƒ15±0.25	ƒ112	25.5±1	175/70R18	TR44
7	3.5JX18H2	5000601027A	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	25.5±1	175/70R18	TR44
8	3.5JX18H2	5000601027A	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	25.5±1	175/70R18	TR44
9	15X6J	4261102121	ƒ54±0.08	4	60°	ƒ14±1	ƒ100	45±1	195/60R15	TR43
10	18X5J	426110211	ƒ54±0.08	4	60°	ƒ14±1	ƒ100	39±1	175/65R14	TR43
11	17X4T	4261142021	ƒ60±0.18±0.03	5	60°	ƒ14±1	ƒ143	40±1	175/70R17	TR43
12	18X4T	426110081	ƒ54±0.18±0.03	4	60°	ƒ14±1	ƒ100	30±1	175/70R16	TR43
13	6JX15H2	1A0116050	ƒ67±0.05	5	60°±1	ƒ15±0.3	ƒ143	50±1	195/65R15	TR44
14	6JX15H2	FQ9965016050	ƒ67±0.05	5	60°±1	ƒ15±0.3	ƒ143	50±1	195/65R15	TR44
15	5.5JX17	FQ9965015570	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	45±1	185/70R17	TR44
16	5JX16	9965105060	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	40±1	185/55R16	TR44
17	5JX16	FQ9965015060	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	40±1	185/55R16	TR44
18	4.5JX20	3101035-0A01	ƒ71.58±0.074	5	螺 2/8+0.2	ƒ15±0.25	ƒ130	22.5±1	145/60R20.05M	TR44
19	4TX17	9965154070	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	35±1	175/70R17	TR44
20	4TX17	FQ9965024070	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	35±1	175/70R17	TR44
21	4TX16	9965414060(国Ⅱ)	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	40±1	175/60R16	TR44
22	3.5JX18H2	3101035-MD	ƒ57±0.134±0.060	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	25.5±1	175/60R18.100M	TR44
23	3.5JX16	3101035-EY	ƒ57.09±0.074	5	螺 2/6±0.3	ƒ15±0.26	ƒ100	38±1	175/60R18.97M	TR44
24	6JX15H2	3101025-EY	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ100	38±1	185/55R16	TR44
25	6JX15H2	3101015-HL	ƒ57.09±0.074	4	螺 2/6+0.2	ƒ15±0.25	ƒ100	38±1	195/50R18.82H	TR44
26	3.5JX17	FQ9965013570	ƒ67±0.5	5	60°±1	ƒ15±0.3	ƒ143	35±1	175/60R17	TR44
27	5JX14	4261142250-A	ƒ60±0.15±0.03	4	60°	ƒ14	ƒ143	50±1	185/70R14	TR44
28	5JX14	4261182260-A	ƒ60±0.15±0.03	4	60°	ƒ14	ƒ143	50±1	185/70R14	TR44
29	5JX14	3101015A861	ƒ54±0.2	4	60°	ƒ15	ƒ100	35±1	195/70R14	TR44
30	5JX14	3101015A705	ƒ60±0.15±0.03	5	60°	ƒ14	ƒ143	50±1	175/70R14	TR44
31	5.008R13	3101015A616	ƒ67±0.5	4	60°	ƒ15	ƒ143	30±1	165/70R13	TR44
32	5.008R13	3101015-ZE2	ƒ54±0.3±0.1	4	60°	ƒ15	ƒ100	45±0.5	155/60R13	TR44
33	4TX16	3101015-A7	ƒ57.09±0.15	5	60°	ƒ14	ƒ143	32±1	175/60R16	TR44
34	5.12JX15	426117B440	ƒ56±0.12	4	60°±1	ƒ14±1	ƒ100	45±1	175/65R15	TR44
35	5.12JX15	426117A460	ƒ60±0.12	5	60°	ƒ14	ƒ143	35±1	195/65R15	TR44
36	5.12JX14	426117A410	ƒ54±0.12	4	60°	ƒ15	ƒ100	42±1	185/70R14	TR44
37	5.12JX14	426117A410	ƒ56±0.12	4	60°	ƒ15	ƒ100	45±1	185/70R14	TR44
38	5.12JX14	3101015B10X	ƒ56±0.12	4	60°	ƒ15	ƒ100	45±1	185/70R14	TR44
39	4.12JX13	426117A400	ƒ56±0.12	4	60°	ƒ14	ƒ100	45±1	165/70R13	TR44
40	4TX16	426117A410	ƒ60±0.2	5	60°	ƒ15	ƒ143	45±1	175/60R16	TR44
41	5.5JX15	5291008300	ƒ60±0.15±0.03	4	60°	ƒ14	ƒ143	50±1	195/60R15	TR44
42	4.5JX20H2	4K0601027	ƒ66.5±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	17±1	145/65R20	TR44
43	6JX17H2	306601027	ƒ57.09±0.074	5	螺 2/6+0.2	ƒ15±0.25	ƒ112	42±1	225/70R17	TR44
44	5JX18H2	30C601027	ƒ57.09±0.074	5	螺 2/6±0.2	ƒ15±0.25	ƒ112	28±1	175/65R18	TR44

COMMERCIAL VEHICLE WHEEL LIST

商用车车轮一览表

序号	规格	合成零件号	中心孔直径	螺栓孔				偏距	配用轮胎型号	
				数量	型式	直径	螺孔直径			分度圆
商用车无内胎车轮										
1	17.5×6.00	13101015-K18-000	Φ163+0.8	6	SR22	Φ32.5	Φ37	Φ222.25	135	9R22.5-14PR
2	19.5×6.75	3101015-10A	Φ221+0.2	8	直孔	Φ24		Φ275	145	225/70R19.5 14PR
3	22.5×6.75	3101015-731/B	Φ221+0.2	8	直孔	Φ24		Φ275	150	225/70R22.5 16PR
4	22.5×6.75	3101015-L15A	Φ214+0.8	8	SR22	Φ32	Φ37	Φ275	152	9R22.5-14PR
5	22.5×7.50	3101015-48A	Φ221+0.2	10	直孔	Φ24		Φ285.75	152.5	11R22.5-14PR
6	22.5×7.50	3101015-L21	Φ220+0.2	10	SR22	Φ32	Φ37	Φ275	152.5	275/70R22.5
7	22.5×7.50	3101015-L11E	Φ220+0.2	10	直孔	Φ26		Φ285.75	152.5	10R22.5
8	22.5×7.50	3101015A55	Φ221+0.2	8	直孔	Φ24		Φ275	152.5	10R22.5 14层级
9	22.5×7.50	3101015K12C	Φ214+0.8	8	SR22	Φ32	Φ37	Φ275	152.5	10R22.5 14层级
10	22.5×8.25	3101015-78A	Φ281+0.2	10	直孔	Φ26		Φ335	165	11R22.5-16PR
11	22.5×8.25	3101015-L11	Φ221+0.2	10	直孔	Φ26		Φ285.75	168	11R22.5-16PR
12	22.5×8.25	3101015-L11A	Φ220+0.2	10	直孔	Φ26		Φ285.75	168	11R22.5-16PR
13	22.5×8.25	253101015C1052	Φ220+0.2	10	直孔	Φ26		Φ285.75	158	275/70R22.5-16PR
14	22.5×9.00	3101015A4E	Φ281+0.2	10	直孔	Φ26		Φ335	175	12R22.5-16PR
15	22.5×13.00	3101015A68R-C00	Φ281+0.2	10	直孔	Φ26		Φ335	0	425/65R22.5 20层级
16	16×5.5K	311A1A01100	Φ140+0.5	6	球孔	Φ20.5		Φ190	47	195/75R16LT
17	16×5.5K	311A1E2A000	Φ162+0.5	6	直孔	Φ24		Φ222.25	63	195/75R16LT
18	22.5×7.50	3101015-48AA	Φ221+0.2	8	直孔	Φ24		Φ275	152.5	10R22.5 14层级
19	22.5×8.25	3101015-V976	Φ281+0.2	10	直孔	Φ26		Φ335	165	11R22.5-16PR
20	22.5×9.00	3101015-1066	Φ281+0.2	10	直孔	Φ26		Φ335	175	12R22.5-16PR
商用车有内胎车轮										
1	6.00G-16	13101015-5K1	Φ163+0.8	6	SSR22	Φ32	Φ37	Φ222.25	136	97.50-16
2	6.00G-16	3101015-902	Φ161+0.2	6		Φ20.5		Φ205	136	7.50-16
3	6.5-16	3101015-V168	Φ163+0.2	6		Φ26		Φ222.25	136	8.25R16
4	6.5-20	3101015-01	Φ214+0.8	8	SR22	Φ32	Φ37	Φ275	145	8.25-20
5	6.5-20	3101015-20A	Φ221+0.2	8		Φ24		Φ275	145	8.25-20
6	7.00T-20	3101015-01R1	Φ214+0.8	8	SR22	Φ32	Φ37	Φ275	152.5	9.00-20
7	7.00T-20	3101015-40A	Φ221+0.2	8		Φ24		Φ275	152.5	9.00-20
8	7.50V-20	3101015R116	Φ220+0.2	10		Φ26		Φ285.75	165	10.00-20
9	7.50V-20	3101015-15W	Φ220+0.2	10		Φ26		Φ285.75	165	10.00-20
10	8.00V-20	3101015-14W	Φ281+0.2	10		Φ26		Φ335	175	11.00R20-16PR
11	8.00V-20	3101015-1H	Φ281+0.2	10		Φ26		Φ335	165	11.00-20
12	8.00V-20	3101015-804	Φ281+0.2	10		Φ26		Φ335	165	11.00-20
13	8.00V-20	3101015-85U	Φ281+0.2	10		Φ26		Φ335	175	11.00R20-16PR
14	8.5-20	3101015-483	Φ281+0.2	10		Φ26		Φ335	178	12.00-20
15	8.5-20	3101015-483J	Φ281+0.2	10		Φ26		Φ335	178	12.00-20

16	8.5-20	3101015-71BJ	Φ281+0.2	10		Φ26		Φ335	186	12.00R20
17	8.5-20	3101015-V751	Φ281+0.2	10		Φ26		Φ335	178	12.00R20
18	8.5-20	3101015-93W	Φ281+0.2	10		Φ26		Φ335	178	12.00R20
19	8.5-24	3101015-900-C00	Φ281+0.2	10		Φ26		Φ335	178	12.00R24
20	10.00-20	3101015A487	Φ281+0.2	10		Φ26		Φ335	230	14.00R20
21	10.0/2.0-25	3101015-946	Φ371+0.2	12		Φ30		Φ425	230	14.00-25
22	10.0/2.0-25	3101015-999	Φ371+0.2	12		Φ30		Φ425	230	14.00-25
23	11.25/2.0-20	3101015-896	Φ281+0.2	10		Φ26		Φ335	0	16.00R20
24	11.25/2.0-20	3101015A896	Φ281+0.2	10		Φ26		Φ335	0	16.00R20
25	12.0/1.7-20	3101015A897	Φ281+0.2	10		Φ26		Φ335	0	13.00R20

Passenger car wheels - List

商用车轻卡车车轮一览表

序号	规格	合成零件号	中心孔直径	螺栓孔				偏距	
				数量	型式	直径	螺孔直径		分度圆
1	22.5×8.25	M431100000054	Φ161+0.2	8	直孔	Φ24		Φ275	165
2	22.5×8.25	M431100000027	Φ220+0.2	10	直孔	Φ26		Φ285.75	165
3	22.5×8.25	M431100000029	Φ221+0.2	8	直孔	Φ24		Φ275	165
4	22.5×7.50	M431100000030	Φ220+0.2	10	直孔	Φ26		Φ285.75	153
5	22.5×7.50	16100311000025	Φ281+0.2	8	直孔	Φ26		Φ275	153
6	22.5×7.50	M431100000020	Φ221+0.2	10	直孔	Φ26		Φ335	158
7	22.5×7.50	1314131100001	Φ220+0.2	10	直孔	Φ26		Φ285.75	152
8	22.5×7.50	L0311050108A0	Φ221+0.2	8	直孔	Φ24		Φ275	150
9	5.5K×16	L131100000060	Φ146+0.2	5	直孔	Φ21		Φ203.2	40
10	5.5K×16	L1311040102A0	Φ146+0.2	5	直孔	Φ21		Φ203.2	120
11	6K×16	L1311040101A0	Φ161+0.2	6	直孔	Φ24		Φ222.25	130
12	7.50V-20	M431100000005	Φ221+0.2	8	直孔	Φ24		Φ275	165
13	7.50V-20	L320831180001	Φ220+0.2	10	直孔	Φ26		Φ285.75	162
14	7.00T-20	M4311030102A0	Φ221+0.2	8	直孔	Φ24		Φ275	153
15	6.5-16	1108931100008	Φ161+0.2	6	直孔	Φ24		Φ222.25	139
16	6.00G-16	L131100000033	Φ161+0.2	6	直孔	Φ24		Φ222.25	130
17	5.5F-16	L0311050128A0	Φ140+0.2	6	直孔	Φ21		Φ190	125
18	5.5F-16	11049311000054	Φ146+0.2	5	直孔	Φ21		Φ203.2	120
19	5.5F-16	1105931100009	Φ163+0.5	6	SR22	Φ32	Φ37	Φ222.25	120