



Technical Data

Item	YJ103
Air tube connection	6 mm
Connection type	Push-in
Working pressure	0.3 - 0.6MPa
Operating temperature	-20 ~ +50°C
Medium	Air
Material	Engineering Plastic

Packing Data

Art. No.	Item	Section	Weight (kg)
P-010-1	YJ103-1	1	0.8
P-010-2	YJ103-2	2	1.0
P-010-3	YJ103-3	3	1.2
P-010-4	YJ103-4	4	1.5
P-010-5	YJ103-5	5	1.8
P-010-6	YJ103-6	6	2.0

Sole distributor:

PT Flowtech Indonesia

Billy Alexander

HP. 0822-3115-8655

Email :

info@flowtechindonesia.com

Usage

YOJE - YJ103 Pneumatic control block installed in the tanker to do the central control by pneumatic, including the emergency foot valve, vapor recovery valve, pipe control valve, API valve, etc. It is available with remote control to cut off the valves under emergency. It can do the quick open and close by pneumatic control block to ensure the loading and unloading more reliable.

Material

Body : Engineering Plastic
 Seal : NBR
 Shaft : Stainless Steel, Copper
 Spring : Stainless Steel
 Cap : PC

Feature

- ◆ Can be combined freely with different sections.
- ◆ Small, compact and robust.
- ◆ Easy to operate.
- ◆ It can not be opened when the air pressure is less than 0.3MPa.
- ◆ Available with automatic closed when air leaked.
- ◆ Be used for several sections.
- ◆ 1/4" NPT with 6 mm air line tubings.
- ◆ Sight glass for checking directive opening and closing.

Installation Diagram

