

Vent valve



Usage

YOJE TQF Vent valve is installed on the top of the tanker. It can automatically control the opening and closing of the gas passage inside and outside the tanker. It ensures reliable respiratory function and maintains tank pressure balance and reduces the oil volatilization losses. It prevents danger and spillage in a roll over situation.

According to GB/T18564: 2006, EN14595 Standard.

Feature

- ◆ Main material is made of plastic or aluminum.
- ◆ The internal roller shows 8 labels.
- ◆ Rotation is locked position by spring to prevent moving.
- ◆ Operated by one hand with any rotation.
- ◆ Used for many sections tankers, separate usage for different fuel.

Install the image



Technical data & packing data

Item	TQF-32	TQF-40	TQF-60	TQF-60D
Positive pressure	6-8 kPa			
Negative pressure	2-3kPa			
Connection mode	15/8-12UN	M60X2	BSPT2"	Flange
Material	Aluminum	Aluminum	Aluminum	Aluminum
Packing size	46X36X30cm	46X36X30cm	46X36X30cm	50x41x33cm
Net weight	18kg	32kg	18kg	19kg
Gross weight	20kg	34kg	20kg	21kg
Packing	36pcs/carton	36pcs/carton	36pcs/carton	20pcs/carton