

Usage

YOJE YJ7306 Series Vapor recovery adaptor is installed on the recovery pipeline on the side tanker with a free float poppet valve. Vapor Recovery hose coupler connects with Vapor Recovery adaptor while opening poppet valve. After completing unloading, the poppet valve remains closed. Dust cap is installed on the adaptor, when not in use, to prevent gasoline vapors from escaping and to prevent water, dust and debris from entering into the tank.

Material

Body: Aluminum
 Seal: NBR
 Shaft: Stainless steel
 Spring: Stainless steel

Feature

- ◆ Aluminum alloy die-cast structure, anodized treatment.
- ◆ 4" female threads by 4" cam and groove.
- ◆ 4" TTMA standard mounting flange.
- ◆ Easy to install.
- ◆ Stainless steel hardware, 3" vapor poppet valve
- ◆ High flow and low pressure drop for quick loading and unloading.
- ◆ Two-position mounting holes for mounting air interlock valve.
- ◆ Meets API RP1004 & EN13083 standard.

Install the image



Technical data & packing data

Item	YJ7306F	YJ7306	YJ7306N	YJ7306
Size	4"	4"	4"	4x3"
Working pressure	0.6MPa			
Operating method	Mechanical			
Temperature range	-20~+70℃			
Connection mode	Flanged	4"NPT	Flanged	3"BSPT
Medium	Diesel, Gasoline, Kerosene			
Packing size	50X50X40cm	41X34X24cm	50X50X40cm	41X34X24cm
Net weight	18kg	13kg	25kg	11kg
Gross weight	20kg	15kg	27kg	13kg
Packing	8pcs/carton	10pcs/carton	8pcs/carton	10pcs/carton